
GRASS KINVARO D-S/D-M FLAP STAY WITH PULL CABLE


This Kinvaro flap stay from Grass has an unobtrusive design for any type of furniture application, with a choice of white or black finish, with integrated damper to open softly. D-M version also includes gentle closing and spring force adjustment.




Install horizontally or vertically



Kinvaro D-S






Kinvaro D-M

Calculation of flap weight: Flap width x flap height x flap thickness x density 1 + weight of handle 2 = weight of flap Densities: MDF board 0.85 kg/dm3, chipboard 0.65 kg/dm3, spruce/pine 0.45 kg/dm3

² Bar handles must be entered with 0.1 kg per 100 mm of handle length. We recommend a trial fitting.

Grass Kinvaro D-S flap stay with pull cable






- > Damped opening
- > Opening angle adjustable via length of pull cable
- > Can be used with shallow cabinets from 82 mm depth
- > Flap height 200-480 mm
- > Unhanded
- > Easy to install horizontally or vertically
- > Cover cap, plastic included
- > Plastic
- > Order qty: 1 pc

	Front	V1 & V2 - installed horizontally or vertically Flap weight including handle (kg)				
	Height					
	(FH)	Spring 40N		Spring 60N		
		1x	2x	1x	2x	
26	200-270	1.7-3.0	3.9-4.5	3.1-4.0	7.5-8.0	
	270-330	1.7-3.0	3.3-4.5	3.1-4.0	6.1-7.4	
	330-380	1.7-1.9	3.2-3.5	2.9-3.5	5.1-6.8	
	380-430	1.5-1.8	2.7-3.3	2.5-3.3	4.8-6.6	
	430-460	1.2-1.7	2.5-31	2.3-3.3	4.6-6.0	
	460-480	-	-	2.2-2.8	4.4-5.3	

Drill position and space required min. 180



FH	Α	В
200 - 270	135	173
270 – 480	148	186

Minimum gap and door protrusion depend on the fitted hinge.





TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2018.

Sprir	g	White	Black
40N		372.90.207	372.90.203
60N		372.90.217	372.90.213

YOU ALSO NEED:



19.02.20/2

