

# LOOX5 12V LED 2091 DOWNLIGHT, MULTI-WHITE

These lights can be used in a variety of different applications thanks to the modular principle with optional bezels for either surface or recess mounting and leads in different lengths. High lumen output with single LED - no LED dots visible.



5

Loox5 12V LED 2091 downlight, Ø 65 mm

Lighting: Loox5 LED



**Modular design -**

Round or square, surface or recess mounting bezels.  
For use with leads with snap-in connector.

- > Equipped with high quality Samsung LEDs
- > For recess mounting, press-fit in Ø 58 mm hole, order bezel separately  
Min. 13.5 mm hole depth required
- > For surface mounting, order bezel separately
- > Colour control only via Häfele Connect Mesh 6-way distributor with multi-white adapter, must be ordered separately
- > Dimmable
- > Degree of protection:  
IP44 as recess mounted downlight  
IP20 as surface mounted downlight
- > Voltage: 12V. Wattage: 3.4W
- > Lead not included, must be ordered separately
- > Silver coloured aluminium housing
- > Order qty: 1 pc

Distance	80°	2700 K	5000 K
250 mm		2000 Lx	2100 Lx
500 mm		520 Lx	550 Lx
750 mm		220 Lx	235 Lx
1000 mm		120 Lx	125 Lx

Output:	2700 - 5000 K
Light colour:	Multi-white
Wattage (W):	3.4
Energy efficiency:	A+
Number of diodes:	12
Light output (Lm):	240 - 270
Efficacy (Lm/W):	72 - 80
Colour Rendering Index:	90



- > The IP44 degree of protection is reduced to IP20 when using a downlight housing, please order lead and housing separately, see page **5.113**
- > Colour control only via 6-way distributor Häfele Connect Mesh with multi-white adapter and remote control or smart phone. Please order separately, shown from page **5.178**

**5 12V**

Multi-White

0-100%

↓ IP20  
↑ IP44

III

F

7  
YEARS

Output	2700 - 5000 K
Cat. No.	833.72.478

**YOU ALSO NEED:**

✓

**DRIVER**  
Page 5.156

✓

**LEAD**  
Page 5.113

✓

**SWITCH**  
Page 5.160-166

✓

**CONTROL**  
Page 5.178-180

✓

**OPTIONAL ACCESSORIES**  
Pages 5.159, 5.167-168