

LOOX 24V LED 3090 DOWNLIGHT, MODULAR, Ø 32.5 MM

Modular downlight - order from choice of four bezel designs in three finishes for surface mounting, or recess mount in Ø 26 mm hole. Downlight includes Samsung LEDs and has a narrow beam angle for staging objects.



5

Lighting: Loox5 LED

Loox5 24V LED 3090 downlight, Ø 32.5 mm



Modular design -
Round or square, surface or recess mounting bezels.
Lead included

- > Equipped with high quality Samsung LEDs
- > With narrow beam angle for staging objects
- > For recess mounting, press-fit in Ø 26 mm hole, order bezel separately
1.7 mm rim, min. 11 mm hole depth required
- > For surface mounting, order bezel separately
- > Voltage: 24V. Wattage: 1.2W
- > Dimmable
- > Degree of protection:
IP44 as recess mounted downlight
IP20 as surface mounted downlight
- > With 2.0 m lead with Loox5 24V connector
- > Aluminium housing
- > Order qty: 1 pc

Output:	2700 K	3000 K	4000 K	5000 K
Light colour:	Warm white	Warm white	Cool white	Cool white
Wattage (W):	1.2	1.2	1.2	1.2
Energy efficiency:	A+	A+	A+	A+
Number of diodes:	1	1	1	1
Light output (Lm):	75	80	80	85
Efficacy (Lm/W):	63	67	67	71
Colour Rendering Index:	90	90	90	90

	55°				
Distance		2700 K	3000 K	4000 K	5000 K
250 mm		825 Lx	870 Lx	935 Lx	940 Lx
500 mm		220 Lx	225 Lx	235 Lx	245 Lx
750 mm		95 Lx	95 Lx	100 Lx	105 Lx
1000 mm		50 Lx	55 Lx	55 Lx	60 Lx



For recess or surface mounting order bezels separately, shown on page 5.139

5 24 V

0-100%

↓ IP20
↑ IP44

III

F

7
YEARS

Finish	2700 k	3000 K	4000 K	5000 K
Silver coloured	833.75.170	833.75.171	833.75.172	833.75.173

YOU ALSO NEED:

✓

DRIVER

Page 5.157

✓

SWITCH

Page 5.160-166

OPTIONAL ACCESSORIES

Pages 5.158-159, 5.167-168, 5.178-181