

LOOX5 24V LED 3092 DOWNLIGHT, MODULAR, Ø 65 MM

These lights can be used in a variety of different applications thanks to the modular principle with optional bezels for either surface or recess mounting. Snap-in lead gives a connection that is secure but also allows the light to be easily released.



5

Lighting: Loox5 LED

Loox5 24V LED 3092 downlight, Ø 65 mm



Modular design -

Round or square, surface or recess mounting bezels.
For use with leads with snap-in connector.

- > Equipped with high quality Samsung LEDs
- > For recess mounting, press-fit in Ø 58 mm hole, order bezel separately 2.6 mm rim, min. 13.5 mm hole depth required
- > For surface mounting, order bezel separately
- > Voltage: 24V. Wattage: 3.4W
- > Dimmable
- > Degree of protection:
 - IP44 as recess mounted downlight
 - IP20 as surface mounted downlight
- > Lead not included, must be ordered separately
- > Silver coloured aluminium housing
- > Order qty: 1 pc

Distance	80°			
	2700 K	3000 K	4000 K	5000 K
250 mm	1870 Lx	1990 Lx	2025 Lx	2135 Lx
500 mm	500 Lx	540 Lx	540 Lx	580 Lx
750 mm	210 Lx	230 Lx	235 Lx	240 Lx
1000 mm	120 Lx	125 Lx	130 Lx	135 Lx

Output:	2700 K	3000 K	4000 K	5000 K
Light colour:	Warm white		Cool white	
Wattage (W):	3.4	3.4	3.4	3.4
Energy efficiency:	A+	A+	A+	A+
Number of diodes:	6	6	6	6
Light output (Lm):	220	240	250	260
Efficacy (Lm/W):	65	71	74	76
Colour Rendering Index:	>90	>90	>90	>90



- > For recess or surface mounting order bezels separately, shown on page 5.137
- > Order lead with snap-in connector separately, shown on page 5.137

5 24 V

0-100%

IP20
IP44

F

7 YEARS

Output	2700 k	3000 K	4000 K	5000 K
Cat. No.	833.75.174	833.75.175	833.75.176	833.75.177

YOU ALSO NEED:

DRIVER
Page 5.157

LEAD
Page 5.137

SWITCH
Page 5.160-166

OPTIONAL ACCESSORIES
Pages 5.158-159, 5.167-168, 5.178-181