

LOOX5 24V LED 3091 DOWNLIGHT, MULTI-WHITE

These lights can be used in a variety of different applications thanks to the modular principle with optional bezels for either surface or recess mounting and leads in different lengths. High lumen output with single LED - no LED dots visible.



5

Loox5 24V LED 3091 downlight, Ø 65 mm



Modular design -

Round or square, surface or recess mounting bezels.
For use with leads with snap-in connector.

- > Equipped with high quality Samsung LEDs
- > For recess mounting, press-fit in Ø 58 mm hole, order bezel separately
Min. 13.5 mm hole depth required
- > For surface mounting, order bezel separately
- > Voltage: 12V. Wattage: 3.4W
- > Colour control only via Häfele Connect Mesh 6-way distributor with multi-white adapter, must be ordered separately
- > Dimmable
- > Degree of protection:
IP44 as recess mounted downlight
IP20 as surface mounted downlight
- > Lead not included, must be ordered separately
- > Silver coloured aluminium housing
- > Order qty: 1 pc

Lighting: Loox5 LED

Distance	80°	2700 K	5000 K
250 mm		2000 Lx	2100 Lx
500 mm		520 Lx	550 Lx
750 mm		220 Lx	235 Lx
1000 mm		120 Lx	125 Lx

Output:	2700 - 5000 K
Light colour:	Multi-white
Wattage (W):	3.4
Energy efficiency:	A+
Number of diodes:	12
Light output (Lm):	240 - 270
Efficacy (Lm/W):	72 - 80
Colour Rendering Index:	90



- > The IP44 degree of protection is reduced to IP20 when using a downlight housing, please order lead and housing separately, see page **5.141**
- > Colour control only via 6-way distributor Häfele Connect Mesh with multi-white adapter and remote control or smart phone. Please order separately, see from page **5.178**

5 24 V

7
YEARS

Output	5000 K
Cat. No.	833.75.178

YOU ALSO NEED:

- DRIVER**
Page 5.157

LEAD
Page 5.141

SWITCH
Page 5.160-166

CONTROL
Page 5.178-180

OPTIONAL ACCESSORIES
Pages 5.159, 5.167-168

TOH DESIGN 2020. © Häfele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice.