HAFELE

LOOX5 24V LED 3050 FLEXIBLE STRIP LIGHT MONOCHROME, CONSTANT CURRENT, 8 MM

The LED 3050 is a constant current flexible strip light with an exceptionally long lifetime and a wattage output of 9.6W per metre, with 700 LEDs per 5 metre strip, ideal as a task light.




An aluminium profile is recommended for installation of 9.6W/m lights, aluminium profiles are shown from page **5.184**



Loox5 24V LED 3050 flexible strip light, constant current, 8 mm width





- Cut LED strip light to length (one contact side remains on the remainder piece; reusable)
- Connect LED strip lights (two contact sides required)
 - C = section length: 50 mm
 - P = length of contact surface: 3.0 mm

- > Equipped with high quality Samsung LEDs
- > For surface mounting, self adhesive, 5 m length
- > Can be shortened every 50 mm
- > Voltage: 24V. Wattage: 48W (9.6W per metre)
- > Dimmable
- > Degree of protection: IP20
- > Lifetime: >70,000 h
- > Width: 8 mm
- > Height: 1.5 mm
- > Lead not included, must be ordered separately
- > White plastic
- > Order qty: 1 pc (roll of 5 m length)

Distance	120°	2700 K	3000 K	4000 K	5000 K			
250 mm		2050 Lx	2150 Lx	2205 Lx	2340 Lx			
500 mm		890 Lx	930 Lx	990 Lx	1010 Lx			
750 mm		490 Lx	520 Lx	545 Lx	550 Lx			
1000 mm		305 Lx	325 Lx	335 Lx	340 Lx			
The values apply to a strip light length of 1 m								

- **O**²
 - Maximum strip length is dependant on driver wattage capacity, shown on page 5.157
 - Maximum recommended strip light length for optimum visual light output: 9.0 m
 - > Lead must be ordered separately, shown on page **5.171**

Output:	2700 K	3000 K	4000 K	5000 K		
Light colour:	Warm white		Cool	white		
Wattage (W):	9.6W per meter					
Energy efficiency:	A+	A+	A+	A+		
Number of diodes:	140 per meter					
Light output (Lm/m):	945	1030	1060	1080		
Efficacy (Lm/W):	98	107	110	113		
CRI Ra / R9:	>90 / >50					













 Length
 2700 K
 3000 K
 4000 K
 5000 K

 5 m
 833.76.362
 833.76.363
 833.76.364
 833.76.365

YOU ALSO NEED:







OPTIONAL ACCESSORIESPages 5.158-159, 5.167-168, 5.178-181