TECHNICAL SPECIFICATION



VDC0024







VDC0024A1SS

VDC0024A1PVDG

STANDARDS







Parallel	arm	Figure	6:

4	8 2 4	1	1	3
---	-------	---	---	---

EN Size Closing force 2-4 Width (mm) 1100 Door size (max) Weight (kg) 80 248 Length (mm) Body dimensions Width (mm) 42 Depth (mm) 51 Door mounted pull side: Reg Fig. 1 Door mounted push side: у Parallel Arm Fig. 66 Application Transom mounted push side: Fig. 61 – 0mm to 50mm frame projection Mechanism Cast aluminium body rack & pinion У Parallel arm bracket Angle of opening 180° Non handed Power adjustment by spring у Power adjustment by position n Adjustable closing speed У Adjustable latch speed У Adjustable backcheck* У Adjustable delayed action* У Grade 3 Corrosion Hours 96 Years 10 Guarantee COVER OPTIONS

Semi-radius	У
Square	n

SUITABILITY

SPECIFICATIONS





* Product outside of CE & Certifire scope with backcheck & delayed action functions enabled.

These functions must not be engaged when product is installed for use on fire doors.

CODE	DESCRIPTION	FINISH	ADDITIONAL INFO.
VDC0024A1SE	Size 2-4 adjustable power door closer	Silver Effect	With cover
VDC0024A1SS	Size 2-4 adjustable power door closer	Satin Stainless	With SS304 Cover
VDC0024A1PVDG	Size 2-4 adjustable power door closer	PVD Gold	With cover
VDC0024A1PS	Size 2-4 adjustable power door closer	Polished Stainless	With cover



For more information please contact us today:

Call: 01228 672900 Fax: 01228 672928

Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk

Vier Design, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH





URS is a member of Registrar of Standards (Holdings) Ltd.