

## Product details

CLIP top standard hinge 107°, overlay application, unsprung, boss: screw-on



|                            |               |
|----------------------------|---------------|
| Part number                | 74T1550.TL    |
| Item number                | 07657333      |
| Colour / finish            | Nickel plated |
| Packaging quantity         | 50 / 250      |
| Weight per 1,000 Pcs in kg | 71.51         |
| EAN code                   | 9002617694826 |
| UPC code                   |               |

### Technical attributes

| Attribute   | Value                         |
|---|-------------------------------|
| application   | standard hinge                |
| Cranking  | Overlay application           |
| Opening angle   | 107                           |
| Closing mechanism                                     | unsprung                      |
| hinge variant   | Special exterior lever        |
| hinge variant   | with free movement for TIP-ON |
| Cover cap type  | 90M2503                       |
| Cover cap type  | 70.1503                       |
| Boss material   | Steel boss                    |
| boss finish   | Nickel plated                 |
| Boss assembly   | screw-on                      |
| Flange width  | 57                            |
| Flange length   | 20                            |
| Flange height   | 3.2                           |
| diametre hinge boss drilling                          | 35                            |
| distance between drillings                            | 45                            |
| eccentric position of fixing holes to hinge boss hole | 9.5                           |
| boss drilling depth                                   | 11.5                          |
| Minimum drilling distance                             | 3                             |
| Maximum drilling distance                             | 6                             |
| arm material  | Steel                         |
| arm finish  | Nickel plated                 |
| collision measurement (hinge arm height)              | 21                            |
| Fixed dimension / factory setting                     | 11                            |
| type of side adjustment                               | With screw                    |
| Side adjustment                                       | +/- 2 mm                      |
| type of depth adjustment                              | convenient with spiral screw  |
| Depth adjustment                                      | + 3/- 2 mm                    |
| Gap   | 1.5                           |
| Item package  | 1 piece                       |
| packaging   | Commercial packing            |