Page 1/9



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

1.1 Product identifier	
Trade name:	Osmo Decking Oil
Article number:	004, 006, 007, 009, 010, 013, 014, 016, 019, 021
1.2 Relevant identified uses of the set of the set of the substance or mixture and uses	he
advised against	No further relevant information available.
Application of the substance / th	he
mixture	Wood treatment
	Coating compound/ Surface coating/ paint
1.3 Details of the supplier of the	e safety data sheet
Manufacturer/Supplier:	Osmo Holz und Color GmbH & Co. KG
	Affhüppen Esch 12
	D-48231 Warendorf
Further information obtainable	
from:	Product safety department
	Phone: +49 (0) 251 / 692 - 188
	Fax: +49 (0) 251 / 692 - 462
	e-mail: helmut.starp@osmo.de
1.4 Emergency telephone	
number:	emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in Germa and English

SECTION 2: Hazards identification

Regulation (EC) No 1272/2008	The product is not classified according to the CLP regulation.
Classification according to	
Directive 67/548/EEC or Directiv	ne e
1999/45/EC	Not applicable.
Information concerning	
particular hazards for human an	d
environment:	The product does not have to be labelled due to the calculation procedure of t
	"General Classification guideline for preparations of the EU" in the latest valid version
Classification system:	The classification is according to the latest editions of the EU-lists and extended
	company and literature data.
2.2 Label elements	
Labelling according to Regulation	n
(EC) No 1272/2008	Void
Hazard pictograms	Void
Signal word	Void
Hazard statements	Void

Page 2/9



GB

Safety data sheet according to 1907/2006/EC, Article 31

inting date 23.03.2015	Version number 15	Revision: 23.03.2015
ade name: Osmo Decking	, Oil	
		(Contd. of page 1)
Precautionary statements	Although this product is not subject to identification reg the safety suggestions are observed.	gulations, we recommend that
	If medical advice is needed, have product container or lab	oel at hand.
	P271 Use only outdoors or in a well-ventilated area.	
	P262 Do not get in eyes, on skin, or on clothing.	
	P501 Dispose of contents/container in accordance w	vith local/regional/national/
	international regulations.	-
Additional information:	Observe the general safety regulations when handling che	micals.
	Always wear a dust mask when sanding.	
	Contains 2-butanonoxime. May produce an allergic reacti	ion.
	Safety data sheet available on request.	
Information concerning		
particular hazards for human		
environment:	Warning:	
	Wash out any used cloth impregnated with this product	immediately after use or store
	in an airtight container (danger of self-ignition)	
2.3 Other hazards		
Results of PBT and vPvB asse		
PBT:	Not applicable.	
vPvB:	Not applicable.	
SECTION 3: Compositio	n/information on ingredients	
~~~~····		
3.2 Mixtures		

Description:	Mixture of substances listed below with nonhazardous additions.		
Dangerous components:			
CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	Xn R65	30-60%
EC number: 918-481-9		R66	
Index number: 649-327-00-6		Asp. Tox. 1, H304	
Reg.nr.: 01-2119457273-39		<b>~</b>	
Additional information:	For the wording of the listed risk ph	rases refer to section 16.	•

### SECTION 4: First aid measures

4.1 Description of first aid m	easures
General information:	Immediately remove any clothing soiled by the product.
	Take affected persons out into the fresh air.
After inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult
	doctor if symptoms persist.
	In case of unconsciousness place patient stably in side position for transportation.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
	(Contd. on page 3)

Page 3/9



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

### Trade name: Osmo Decking Oil

	(Contd. of page 2)
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
4.2 Most important symptoms and	1
effects, both acute and delayed	Headache
	Disziness
4.3 Indication of any immediate	
medical attention and special	
treatment needed	No further relevant information available.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing agents:	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
For safety reasons unsuitable	
extinguishing agents:	Water with full jet
5.2 Special hazards arising from	
the substance or mixture	Formation of toxic gases is possible during heating or in case of fire.
5.3 Advice for firefighters	
Protective equipment:	Mouth respiratory protective device.
Additional information	Dispose of fire debris and contaminated fire fighting water in accordance with official
	regulations.
	Cool endangered receptacles with water spray.

### **SECTION 6:** Accidental release measures

6.1 Personal precautions, protective equipment and	
emergency procedures	Wear protective equipment. Keep unprotected persons away.
	Keep away from ignition sources.
	Ensure adequate ventilation
6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for	
containment and cleaning up:	Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
6.4 Reference to other sections	See Section 13 for disposal information.
	No dangerous substances are released.

### SECTION 7: Handling and storage

7.1 Precautions for safe handling	Keep away from heat and direct sunlight.	
	Keep receptacles tightly sealed.	
	Use only in well ventilated areas.	
		anti an naga ()

Page 4/9



### Safety data sheet according to 1907/2006/EC, Article 31

Version number 15

Tr	Trade name: Osmo Decking Oil		
		Prevent formation of aerosols.	
	Information about fire - and		
	explosion protection:	Keep ignition sources away - Do not smoke.	
	7.2 Conditions for safe storage, in Storage:	cluding any incompatibilities	
	Requirements to be met by		
	storerooms and receptacles:	Store in a cool location.	
	*	Store only in the original receptacle.	
	Information about storage in one		
	common storage facility:	Do not store together with alkalis (caustic solutions).	
		Do not store together with oxidising and acidic materials.	
	Further information about		
	storage conditions:	Keep container tightly sealed.	
		Store in cool, dry conditions in well sealed receptacles.	
	Storage class:	10	
	7.3 Specific end use(s)	No further relevant information available.	
	SECTION 8: Exposure cont	trols/personal protection	
	Additional information about		
	design of technical facilities:	No further data; see item 7.	
		, ,	
	8.1 Control parameters		
	Ingredients with limit values that	require monitoring at the workplace:	
	64742-48-9 aliphatic hydrocarbo	ns, C10-C13	
	TWA (8 H) Long-term value: 1.00	00 mg/m ³ , 150 ppm ppm	
	Source: UK SIA		
	Additional information:	The lists valid during the making were used as basis.	
	-	-	
	8.2 Exposure controls		
	Personal protective equipment: General protective and hygienic		
	General protective and hygienic measures:	Immediately remove all soiled and contaminated clothing	
	<i>тсизи</i> сз.	mineuratery remove an soneu and contaminated clothing	

8.2 Exposure controls	
Personal protective equipment:	
General protective and hygienic	
measures:	Immediately remove all soiled and contaminated clothing
	Keep away from foodstuffs, beverages and feed.
	Avoid contact with the eyes and skin.
	Do not eat, drink, smoke or sniff while working.
	Do not carry product impregnated cleaning cloths in trouser pockets.
Respiratory protection:	Use suitable respiratory protective device only when aerosol or mist is formed.
	Not necessary if room is well-ventilated.
Protection of hands:	To avoid skin problems reduce the wearing of gloves to the required minimum.
	Selection of the glove material on consideration of the penetration times, rates of
	diffusion and the degradation
	The glove material has to be impermeable and resistant to the product/ the substance/
	the preparation.

(Contd. on page 5)

Printing date 23.03.2015

(Contd. of page 3)

GB

Revision: 23.03.2015

Page 5/9



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

### Trade name: Osmo Decking Oil

	(Contd. of page
Material of gloves	Nitrile rubber, NBR
00	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the permanent contact gloves	
made of the following materials	
are suitable:	Nitrile rubber, NBR
	Recommended thickness of the material: $\geq 0.4$ mm
As protection from splashes	
gloves made of the following	
materials are suitable:	Nitrile rubber, NBR
Eye protection:	Goggles recommended during refilling
Body protection:	Protective work clothing

### **SECTION 9: Physical and chemical properties**

General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Mild
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 180 °C
Flash point:	> 62 °C (DIN EN ISO 2719)
Ignition temperature:	240 °C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures a
	possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Density at 20 °C:	0.85 - 1.0 g/cm ³ (DIN 51757)
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Viscosity:	
Kinematic at 20 °C:	25-50 s (DIN 53211/3mm)
	>21 mm²/s (40 °C)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

	(Contd. of pa
Solvent content:	
VOC (EC)	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))
9.2 Other information	No further relevant information available.
SECTION 10: Stability and	l reactivity
10.1 Reactivity	
10.2 Chemical stability	
Thermal decomposition /	
conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous	•
reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition	
products:	Carbon monoxide and carbon dioxide
	Nitrogen oxides (NOx)
Additional information:	Warning:
	Wash out any used cloth impregnated with this product immediately after use or s
	in an airtight container (danger of self-ignition)
SECTION 11: Toxicologica	-1 : C

LD/LC50 values relevant for classification:

64742-48-9 aliphatic hydrocarbons, C10-C13

OralLD50>2000 mg/kg (rat)DermalLD50>2000 mg/kg (rat)InhalativeLC50 / 4h>5 mg/l (rat)

### 96-29-7 2-butanonoxime

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50 / 4h	20 mg/l (rat)

Primary irritant effect:		
on the skin:	At long or repeated contact with skin it may cause dermatitis due to	the degreasing
	effect of the solvent.	
on the eye:	not tested	
Sensitisation:	Sensitising effect by skin contact is possible by prolonged exposure.	
		(Contd. on nago 7)

(Contd. on page 7)



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

GB

	(Contd. of page
Additional toxicological information: Sensitisation	The product is not subject to classification according to the calculation method of General EU Classification Guidelines for Preparations as issued in the latest version When used and handled according to specifications, the product does not have harmful effects to our experience and the information provided to us. Contains 2-butanonoxime. May produce an allergic reaction.
SECTION 12: Ecological	information
12.1 Toxicity	•
Aquatic toxicity:	
64742-48-9 aliphatic hydrocar	bons, C10-C13
EC50 / 48h >1000 mg/l (daphn	
IC50 / 72h >1000 mg/l (algae)	
LC50 / 96h >1000 mg/l (fish)	
	<i>ility</i> No further relevant information available.
12.2 Persistence and degradable 12.3 Bioaccumulative potential	
12.5 Dioaccumulative potential 12.4 Mobility in soil	No further relevant information available.
Additional ecological informati	
General notes:	Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous water
	Do not allow product to reach ground water, water course or sewage system.
12.5 Results of PBT and vPvB	
PBT:	Not applicable.
vPvB: 12.6 Other adverse effects	Not applicable. No further relevant information available.
SECTION 13: Disposal co	onsiderations
13.1 Waste treatment methods	
Recommendation	Must not be disposed together with household garbage. Do not allow product to resewage system.
European waste catalogue	
08 01 11* waste paint and varm	ish containing organic solvents or other dangerous substances
15 01 10* packaging containing	g residues of or contaminated by dangerous substances



### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

(Contd. of page 7)

# Trade name: Osmo Decking Oil

Recommended cleansing agents: Solvent naphtha

### **SECTION 14: Transport information** 14.1 UN-Number ADR, ADN, IMDG, IATA Void 14.2 UN proper shipping name ADR, ADN, IMDG, IATA Void 14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Void Class 14.4 Packing group Void ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. UN "Model Regulation":

### SECTION 15: Regulatory information

 15.1 Safety, health and

 environmental regulations/

 legislation specific for the

 substance or mixture
 No further relevant information available.

 15.2 Chemical safety assessment:
 A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Relevant phrases H304 May be fatal if swallowed and enters airways. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. Department issuing MSDS: product safety department Hr. Dr. Starp (Contd. on page 9)

- GB

Page 9/9



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 23.03.2015

Version number 15

Revision: 23.03.2015

## Trade name: Osmo Decking Oil

Abbreviations and acronyms:	ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreen
	concerning the International Carriage of Dangerous Goods by Road)
	IMDG: International Maritime Code for Dangerous Goods
	IATA: International Air Transport Association
	GHS: Globally Harmonised System of Classification and Labelling of Chemicals
	EINECS: European Inventory of Existing Commercial Chemical Substances
	ELINCS: European List of Notified Chemical Substances
	CAS: Chemical Abstracts Service (division of the American Chemical Society)
	VOC: Volatile Organic Compounds (USA, EU)
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
	Asp. Tox. 1: Aspiration hazard, Hazard Category 1
* Data compared to the previous	
version altered.	