

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **4006 Osmo Wood Protector, Clear**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture No further relevant information available.

Priming
 Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
 Affhüppen Esch 12
 D-48231 Warendorf

Further information obtainable from:

Product safety department
 Phone: +49 (0) 251 / 692 - 188
 Fax: +49 (0) 251 / 692 - 462
 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.

Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system: The classification is according to the latest editions of the EU-lists and extended by company and literature data.

2.2 Label elements**Labelling according to Regulation**

(EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Precautionary statements Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

(Contd. on page 2)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 1)

Additional information:

Keep out of reach of children.
 If medical advice is needed, have product container or label at hand.
 P271 Use only outdoors or in a well-ventilated area.
 P262 Do not get in eyes, on skin, or on clothing.
 P501 Dispose of contents/container in accordance with local/regional/national/
 international regulations.
 Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.
 Contains 2-butanonoxime. May produce an allergic reaction.
 Safety data sheet available on request.

**Information concerning
 particular hazards for human and
 environment:**

Warning:
 Wash out any used cloth impregnated with this product immediately after use or store
 in an airtight container (danger of self-ignition)
 Observe the general safety regulations when handling chemicals.
 Always wear a dust mask when sanding.

2.3 Other hazards**Results of PBT and vPvB assessment**




PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

| | | | |
|----------------------------|---------------------------------|--|--------|
| CAS: 64742-48-9 | aliphatic hydrocarbons, C10-C13 |  Xn R65  R66  Asp. Tox. 1, H304 | 30-60% |
| EC number: 918-481-9 | | | |
| Index number: 649-327-00-6 | | | |
| Reg.nr.: 01-2119457273-39 | | | |

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.
 Take affected persons out into the fresh air.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.

(Contd. on page 3)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 2)

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed Dizziness
Headache

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation
Keep away from ignition sources.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 13 for disposal information.

No dangerous substances are released.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.
Keep receptacles tightly sealed.
Keep away from heat and direct sunlight.

(Contd. on page 4)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 3)

Information about fire - and explosion protection: Prevent formation of aerosols.
 Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities
Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
 Store in a cool location.

Information about storage in one common storage facility: Do not store together with alkalis (caustic solutions).
 Do not store together with oxidizing and acidic materials.

Further information about storage conditions: Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

| | |
|-----------|--|
| TWA (8 H) | Long-term value: 1.000 mg/m ³ , 150 ppm ppm Source: UK SIA |
|-----------|--|

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
 Do not carry product impregnated cleaning cloths in trouser pockets.
 Immediately remove all soiled and contaminated clothing
 Keep away from foodstuffs, beverages and feed.
 Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.
 Use suitable respiratory protective device only when aerosol or mist is formed.
 Short term filter device:
 Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 °C)).

Protection of hands:

Protective gloves
 To avoid skin problems reduce the wearing of gloves to the required minimum.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 4)

| | |
|--|--|
| Material of gloves | Nitrile rubber, NBR |
| Penetration time of glove material | The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. |
| For the permanent contact gloves made of the following materials are suitable: | Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm |
| For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: | Nitrile rubber, NBR |
| As protection from splashes gloves made of the following materials are suitable: | Nitrile rubber, NBR |
| Eye protection: | Goggles recommended during refilling |
| Body protection: | Protective work clothing |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

| | |
|----------------|------------|
| Form: | Viscous |
| Colour: | Colourless |
| Odour: | Mild |

Change in condition

| | |
|-------------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | > 180 °C |

Flash point: > 61 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

| | |
|---------------|-----------|
| Lower: | 0.6 Vol % |
| Upper: | 7.0 Vol % |

Density at 20 °C: 0.8 - 0.9 g/cm³ (DIN 51757)

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

(Contd. on page 6)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 5)

Viscosity:

Kinematic at 20 °C: 25 - 35 s (DIN 53211/4)
 > 30 s (ISO 3mm)

Solvent content:

VOC (EC) < 750 g/l (VOC-max. = 750 g/l (2010 A/h))
9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity**10.2 Chemical stability**

**Thermal decomposition /
 conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous
 reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

**10.6 Hazardous decomposition
 products:**

Formation of toxic gases is possible during heating or in case of fire.
 Nitrogen oxides (NO_x)
 Carbon monoxide and carbon dioxide

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store
 in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity:****LD/LC50 values relevant for classification:****64742-48-9 aliphatic hydrocarbons, C10-C13**

| | | |
|------------|-----------|-------------------------------|
| Oral | LD50 | > 5000 mg/kg (rat) (OECD 401) |
| Dermal | LD50 | > 5000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h | > 5 mg/l (rat) (OECD 403) |

96-29-7 2-butanonoxime

| | | |
|------------|-----------|----------------------|
| Oral | LD50 | 3700 mg/kg (rat) |
| Dermal | LD50 | 200-2000 mg/kg (rat) |
| Inhalative | LC50 / 4h | >10.5 mg/l (rat) |

(Contd. on page 7)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 6)

Primary irritant effect:**on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

on the eye:

No irritating effect.

Sensitization:

Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Sensitisation

Contains 2-butanonoxime. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:****64742-48-9 aliphatic hydrocarbons, C10-C13**

EC50 / 48h > 1000 mg/l (daphnia) (OECD 202)

EC50/ 72h > 1000 mg/l (algae) (OECD 201)

LC50 / 96h > 1000 mg/l (fish) (OECD 203)

96-29-7 2-butanonoxime

EC50 / 48h 201 mg/l (daphnia)

IC50 / 72h 11.8 mg/l (algae)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Behaviour in sewage processing plants:****96-29-7 2-butanonoxime**

EC50/ 96h >100 mg/l (fish)

Additional ecological information:**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment**PBT:**

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

| | |
|----------|---|
| 08 01 11 | waste paint and varnish containing organic solvents or other dangerous substances |
| 15 01 10 | packaging containing residues of or contaminated by dangerous substances |

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

UN "Model Regulation":

-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

GISBAU-Code

GISCODE: M-GF02

VOC (EC)

< 750 g/l (VOC-max. = 750 g/l (2010 A/h))

(Contd. on page 9)

Safety data sheet
 according to 1907/2006/EC, Article 31

Printing date 16.10.2014

Version number 13

Revision: 16.10.2014

Trade name: 4006 Osmo Wood Protector, Clear

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Department issuing MSDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

*** Data compared to the previous version altered.**