

Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name:

1101 Osmo Wood Wax Finish Clear Extra Thin

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

*mixture* Coating compound/ Surface coating/ paint

Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

*from:* Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

### SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

**Regulation** (EC) No 1272/2008 The product is not classified according to the CLP regulation.

Classification according to

Directive 67/548/EEC or Directive

1999/45/EC Not applicable.

Information concerning

particular hazards for human and

environment: The product does not have to be labelled due to the calculation procedure of the

"General Classification guideline for preparations of the EU" in the latest valid version.

Classification system: The classification is according to the latest editions of the EU-lists and extended by

company and literature data.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008 Void
 Hazard pictograms Void
 Signal word Void
 Hazard statements Void

**Precautionary statements**Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed.

(Contd. on page 2)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 1)

Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

P271 Use only outdoors or in a well-ventilated area. P262 Do not get in eyes, on skin, or on clothing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information: Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

Contains 2-butanonoxime. May produce an allergic reaction.

Information concerning

particular hazards for human and

environment: Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

### SECTION 3: Composition/information on ingredients

3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

| Dangerous components:      |                                 |                            |        |
|----------------------------|---------------------------------|----------------------------|--------|
| CAS: 64742-48-9            | aliphatic hydrocarbons, C10-C13 | Xn R65                     | 30-60% |
| EC number: 918-481-9       |                                 | R66                        |        |
| Index number: 649-327-00-6 |                                 | <b>♦</b> Asp. Tox. 1, H304 |        |
| Reg.nr.: 01-2119457273-39  |                                 |                            |        |
|                            |                                 |                            |        |

**Additional information:** For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 2)

4.2 Most important symptoms and

effects, both acute and delayed Disziness

Headache

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents:

Water with full jet

5.2 Special hazards arising from

the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

*emergency procedures* Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

**6.4 Reference to other sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.

Use only in well ventilated areas. Keep receptacles tightly sealed. Prevent formation of aerosols.

(Contd. on page 4)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 3)

Information about fire - and

*explosion protection:* Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

storage conditions: Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

Storage class: VCI storage class (VCI = German Association of the Chemical Industry): 10

**7.3** *Specific end use(s)* No further relevant information available.

### SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1.000 mg/m³, 150 ppm ppm

Source: UK SIA

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:** Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

Short term filter device:

Filter A/P2

**Protection of hands:** Protective gloves

To avoid skin problems reduce the wearing of gloves to the required minimum.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

(Contd. on page 5)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 4)

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4$  mm

For the permanent contact of a maximum of 15 minutes gloves made of the following materials

are suitable: Nitrile rubber, NBREye protection: If risk of splashing:

Safety glasses according to EN 166:2001 (e.g. densely closing frame glasses with side

protection)

**Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Appearance:

Form: Fluid
Colour: Colourless
Odour: Mild

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 180 °C

Flash point: > 62 °C (DIN EN ISO 2719)

*Ignition temperature:* 240 °C

**Self-igniting:** Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are

possible.

Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

**Density at 20 °C:** 0.83-0.87 g/cm<sup>3</sup>

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

(Contd. on page 6)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 5)

Viscosity:

Dynamic: Not determined. Kinematic:  $>21 \text{ mm}^2/\text{s} (40 \, ^{\circ}\text{C})$ 

Solvent content:

VOC (EC) Not applicable.

9.2 Other information No further relevant information available.

## SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions

Reacts with fabric soaked in the product (e.g. cleaning wool).

No further relevant information available. 10.4 Conditions to avoid No further relevant information available. 10.5 Incompatible materials:

10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

## SECTION 11: Toxicological information

LC50 / 4h > 10.5 mg/l (rat)

## 11.1 Information on toxicological effects

Acute toxicity:

Inhalative

| LD/LC50    | LD/LC50 values relevant for classification: |                               |  |  |
|------------|---|-------------------------------|--|--|
| 64742-48-  | 64742-48-9 aliphatic hydrocarbons, C10-C13  |                               |  |  |
| Oral       | LD50  | > 5000 mg/kg (rat) (OECD 401) |  |  |
| Dermal     | LD50  | > 5000 mg/kg (rat) (OECD 402) |  |  |
| Inhalative | LC50 / 4h                                   | > 5 mg/l (rat) (OECD 403)     |  |  |
| 96-29-7 2  | 96-29-7 2-butanonoxime                      |                               |  |  |
| Oral       | LD50  | 3700 mg/kg (rat)              |  |  |
| Dermal     | LD50  | 200-2000 mg/kg (rat)          |  |  |

(Contd. on page 7)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 6)

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing

effect of the solvent.

on the eye: not tested

Sensitisation: Sensitising effect by skin contact is possible by prolonged exposure.

Additional toxicological

*information:* The product is not subject to classification according to the calculation method of the

General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any

harmful effects to our experience and the information provided to us.

Sensitisation Contains 2-butanonoxime. May produce an allergic reaction.

### SECTION 12: Ecological information

#### 12.1 Toxicity

| 4 | . •   |          |   |
|---|-------|----------|---|
| A | าเกลา | toxicity | • |
|   |       |          |   |

## 64742-48-9 aliphatic hydrocarbons, C10-C13

EC50 / 48h | > 1000 mg/l (daphnia) (OECD 202)

EC50/72h |> 1000 mg/l (algae) (OECD 201)

LC50 / 96h | > 1000 mg/l (fish) (OECD 203)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

*PBT*: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

| European waste catalogue |   |  |
|--------------------------|---|--|
| 08 01 11                 | waste paint and varnish containing organic solvents or other dangerous substances |  |
| 15 01 10                 | packaging containing residues of or contaminated by dangerous substances          |  |

(Contd. on page 8)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 7)

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

### SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

*Class* Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II of

*MARPOL73/78 and the IBC Code* Not applicable.

UN "Model Regulation":

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture No further relevant information available.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

*Relevant phrases* H304 May be fatal if swallowed and enters airways.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 9)



Printing date 26.02.2015 Version number 15 Revision: 26.02.2015

## Trade name: 1101 Osmo Wood Wax Finish Clear Extra Thin

(Contd. of page 8)

**Department issuing MSDS:** product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent Asp. Tox. 1: Aspiration hazard, Hazard Category 1

\* Data compared to the previous

version altered.

GB