

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **4005 Osmo WR Base Coat AQUA, clear**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Wood-preservative impregnation
Paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG
Affhüppen Esch 12
D-48231 Warendorf

Further information obtainable from:

Product safety department
Phone: +49 (0) 251 / 692 - 188
Fax: +49 (0) 251 / 692 - 462
e-mail: helmut.starp@osmo.de

1.4 Emergency telephone number:

-
emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

Void

Signal word

Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 1)

Additional information: Contains propiconazole. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	10-25%
CAS: 60207-90-1 EINECS: 262-104-4 Index number: 613-205-00-0	propiconazole ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<1%

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Disziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 2)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

The product is not flammable.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

(Contd. on page 4)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 3)

Further information about storage conditions:

Protect from frost.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

34590-94-8 (2-methoxymethylethoxy)propanol

WEL	Long-term value: 308 mg/m ³ , 50 ppm
Sk	

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.
Immediately remove all soiled and contaminated clothing
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2

Protection of hands:

Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 4)

*For the permanent contact gloves
made of the following materials
are suitable:*

Nitrile rubber, NBR

*As protection from splashes
gloves made of the following
materials are suitable:*

Nitrile rubber, NBR

Eye protection:

Goggles recommended during refilling

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: Colourless

Odour: Mild

pH-value at 20 °C: 4 - 4.3

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 100 °C

Flash point: > 100 °C

Self-igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density at 20 °C: 1.0 - 1.05 g/cm³

**Solubility in / Miscibility with
water:**

Fully miscible.

Viscosity:

Kinematic at 20 °C: 50 - 55 s (ISO 2mm)

9.2 Other information No further relevant information available.

(Contd. on page 6)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 5)

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition /

conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions

No dangerous reactions known.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition

products:

No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD/LC50 values relevant for classification:

60207-90-1 propiconazole

Oral	LD50	1517 mg/kg (rat) (OECD- Prüfrichtlinie 401)
Dermal	LD50	> 4000 mg/kg (rat)
Inhalative	LC50 / 4h	5.8 mg/l (rat) (403 Acute Inhalation Toxicity)

Primary irritant effect:

Skin corrosion/irritation

No irritant effect.

Serious eye damage/irritation

not tested

Respiratory or skin sensitisation

Sensitisation possible through skin contact.

Sensitisation

Contains propiconazole. May produce an allergic reaction.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

60207-90-1 propiconazole

EC50 / 48h	10.2 mg/l (daphnia) (202 Daphnia sp. acute Immobilization)
EC50/ 72h	9 mg/l (algae) (201 Alga Growth, Inhibition Test (Biomasse))
LC50 / 48h	10.2 mg/l (fish)
LC50 / 96h	4.3 mg/l (fish) (203 Fish Acute Toxicity)

(Contd. on page 7)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 6)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Harmful to fish

Additional ecological information:

General notes: Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

03 02 02	organochlorinated wood preservatives
15 01 10	packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

(Contd. on page 8)

*

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 7)

14.4 Packing group
ADR, IMDG, IATA

Void

14.5 Environmental hazards:
Marine pollutant:

No

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of
MARPOL73/78 and the IBC Code

Not applicable.

UN "Model Regulation":

-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Marking in accordance with biocide guideline 98/8/EG

60207-90-1 | propiconazole

9.0 g/kg

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

Department issuing MSDS:

product safety department

Contact:

Hr. Dr. Starp

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

(Contd. on page 9)

Material Safety Data Sheets
according to 1907/2006/EC, Article 31

Printing date 04.08.2015

Version number 2

Revision: 04.08.2015

Trade name: 4005 Osmo WR Base Coat AQUA, clear

(Contd. of page 8)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

*** Data compared to the previous
version altered.**