



**SAFETY DATA SHEET**  
SOLID WOOD HARD WAX WORKTOP OIL

Page: 1

Compilation date: 01/02/2015

Revision No: 3

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** SOLID WOOD HARD WAX WORKTOP OIL

**Product code:** HWWOIL

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Unika Color Products Ltd

Unika House

New York Way

New York Industrial Park

Newcastle upon Tyne

NE27 0QF

United Kingdom

**Tel:** +44 (0) 191-259-0033

**Fax:** +44 (0) 191-257-4525

**Email:** [technical@unika.co.uk](mailto:technical@unika.co.uk)

**1.4. Emergency telephone number**

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** -: EUH208; -: EUH210

**Most important adverse effects:** Contains 2-butanone oxime. May produce an allergic reaction. Safety data sheet available on request.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** EUH208: Contains 2-butanone oxime. May produce an allergic reaction.

EUH210: Safety data sheet available on request.

**Precautionary statements:** P102: Keep out of reach of children.

**2.3. Other hazards**

**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**

[cont...]

**SAFETY DATA SHEET**  
SOLID WOOD HARD WAX WORKTOP OIL

Page: 2

**3.2. Mixtures**

**Hazardous ingredients:**

HYDROCARBONS, C11-14, N-/ISO-/CYCLOALKANES, <2% AROMATICS

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304; -: EUH066	10-30%

HYDROCARBONS, C10-13, N-/ISO-/CYCLOALKANES, <2% AROMATICS

918-481-9	-	-	Asp. Tox. 1: H304; -: EUH066	10-30%
-----------	---	---	------------------------------	--------

2-BUTANONE OXIME

202-496-6	96-29-7	-	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%
-----------	---------	---	---	-----

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Do NOT use solvents or thinners.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor. Do not induce vomiting.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

**Delayed / immediate effects:** No symptoms.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Immediate / special treatment:** Not applicable.

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Alcohol resistant foam. Carbon dioxide. Water spray.

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** In combustion emits toxic fumes.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

**SAFETY DATA SHEET**  
SOLID WOOD HARD WAX WORKTOP OIL

Page: 3

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**6.4. Reference to other sections**

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Ensure there is sufficient ventilation of the area. Use non-sparking tools. Smoking is forbidden.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**HYDROCARBONS, C11-14, N-/ISO-/CYCLOALKANES, <2% AROMATICS**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	566mg/m3	850mg/m3

**HYDROCARBONS, C10-13, N-/ISO-/CYCLOALKANES, <2% AROMATICS**

UK	-	-	566mg/m3	850ml/m3
----	---	---	----------	----------

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

[cont...]

**SAFETY DATA SHEET**  
SOLID WOOD HARD WAX WORKTOP OIL

Page: 4

**8.2. Exposure controls**

**Engineering measures:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Straw

**Odour:** Barely perceptible odour

**Viscosity:** Oily

**Boiling point/range°C:** 200

**Flammability limits %: lower:** 1

**upper:** 8

**Flash point°C:** 70

**Relative density:** 0.9

**VOC g/l:** 275

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

[cont...]

**SAFETY DATA SHEET**  
SOLID WOOD HARD WAX WORKTOP OIL

Page: 5

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**2-BUTANONE OXIME**

ORL	MUS	LD50	1	gm/kg
ORL	RAT	LD50	930	mg/kg
SCU	RAT	LD50	2702	mg/kg

**Toxicity values:** No data available.

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** No symptoms.

**Delayed / immediate effects:** No symptoms.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Not biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** Bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

**SAFETY DATA SHEET**  
SOLID WOOD HARD WAX WORKTOP OIL

Page: 6

**Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.  
EUH210: Safety data sheet available on request.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.